

Contact:

Susan L Doyle, Marketing
susan.doyle@appliedmach.com

For Immediate Release

Compact and Nimble. The Versatile Merlo P27.6 Plus

It may be compact but the Merlo P27.6Plus supplies expansive capabilities. This compact machine (12'10' x 6'0"x 6'5") with its 10" ground clearance supplies a 6,000 lbs. maximum load capacity. Its no-flex boom lifts smoothly to 19'4" and easily handles 3,300 lbs. The maximum reach of 10'9" safely carries 2,000 lbs.

Forks are standard. The P27.6 Plus easily accepts buckets up to 2.2 cu/yd. (light material) plus any number of other attachments. The easy to add skid steer adaptor, along with the hydraulic service on the boom, expands its attachment capabilities.

The P27.6 Plus has the largest cab in its class (3'3"). It has a wide glass surface (360° view) for optimal viewing. This FOPS and ROPS certified cab is designed with a maximum level of ergonomic seating and dashboard layout, including its single-lever joystick. Heat and AC are standard. Cab airflow is optimized by the side mounted air filter.

The P27.6Plus nimbleness comes from its 4WD/3 steering modes, 11' turning a ratio, and hydrostatic transmission. Its quick response 25mph is powered by a 4-cylinder 75Hp Kubota engine. Standard features include work and travel lights, pedal inching control for precise load placement, Tac-lock system for in-cab control of attachment change out, and reversible fan for optimal engine performance.

##

Applied Machinery Sales imports and distributes Merlo telehandlers for the USA market. Located in Rock Hill, SC, AMS offers direct sales, rentals, dealership opportunities and financing. To learn more, please contact us: 803-327-4949, info@appliedmach.com, web: ams-merlo.com.

