



Marketing Contact: Susan L. Doyle  
Applied Machinery Sales  
[marketing@applieddmach.com](mailto:marketing@applieddmach.com)  
803-327-4949

## High innovation. High performance. Merlo TF30.9.

Merlo's TF30.9 telehandler is engineered to deliver more power and versatility in a compact telehandler.

It offers a maximum load capacity of 6,600 lbs., with a maximum boom height of 28'3" that safely lifts 2,400 lbs. The no-flex boom can effortlessly handle 1,200 lbs. at a maximum reach of 18'8". This machine is compact (14'3" x 6'9" x 6'11") and lightweight (14,770 lbs.).

The cab is designed for optimum operator comfort and efficiency. Its 3'3" space provides ergonomic seating, controls and intuitive joystick. This cab has a very large glass surface (46sq/ft.) for 360 degree view of the site and load at all times. AC is standard. The cab design includes side mounted air filtration which prevents the entry of dust into the cab.



Forks are standard. The TF30.9 easily accepts buckets up to 3.2 cu/yd. (light material) plus any number of other attachments. An easy to add skid steer adaptor, along with the hydraulic service on the boom, expands its attachment capabilities.

Its low height, pressurized cab, and nimble maneuverability have led this Merlo Telehandler to become popular with poultry farming.

*We work 7 days a week, depending on weather. We clean out over 75% of the chicken houses here in Jackson County, GA. We had a Caterpillar before, but now with this Merlo, it's like going from a Volkswagen to a Cadillac. It's sturdier and I just felt safe and comfortable even before I turned the key for the first time. This machine [TF30.9 with 3.2 cu/yd. bucket] fits just perfect through the doorways. It's airtight; I take my dog with me. Its quiet compared to what I had before. I am so happy with this piece of machinery. I wish every piece we had was a Merlo." - S. Spence, Justin Weeks Farm, GA*

The nimble maneuverability comes from its 4WD/3 steering modes, tight 12'10" turning ratio, and hydrostatic transmission. Its quick response 25mph is powered by a 4-cylinder 115 Hp Deutz engine. Fan Drive technology is standard. It allows the operator to change the engine fan's rotation direction from venting, which cools the radiators, to blowing, which cleans the radiators, eliminating dust and residue collected during the work phase.

Standard features also include: built in safety system that monitors and manages machine parameters in real time; work and travel lights; pedal inching control for precise load placement; and, a Tac-lock system for in-cab control of attachment change out.

##

Applied Machinery Sales imports and distributes Merlo telehandlers for the USA market. Located in Rock Hill, SC, AMS offers direct sales, rentals, dealership opportunities and financing. To learn more, please contact us: 803-327-4949, [info@appliedmach.com](mailto:info@appliedmach.com), web: [ams-merlo.com](http://ams-merlo.com).